## Drill press bench model

13 mm self-locking chuck - h 650 mm

F11-951





Drill press with laser pointing and aluminium pulley drive for better performances.

- Distance between the chuck and the column of 104 mm.
- Self-locking chuck capacity from 0 to 13 mm.
- 5 speeds from 580 to 2650 RPM.
- Chuck travel 50 mm
- Workbench with lateral extensions.
- Quick-locking vice.
- Adjustable drilling depth stop with laser pointing device.
- Silent operation thanks to the aluminum pulleys.
- Easy-to-use circular handle with three knobs.
- Tilting workbench with grooves for a vice fixing.
- Top line height 650 mm

Standard equipment: chuck protection, workbench vice and laser pointing device.

## **TECHNICAL FEATURES**

Motor:	350 W - 230 V
Rotation speed :	1400 RPM
5 Speeds:	580 ÷ 2650 RPM
Workbench:	193 x 160 mm - 45° tilting, with extensions
Extensions up to:	273 x 160 mm
Laser power:	< 1 mW

Taper :	B16
Column diameter:	50 mm
Chuck travel:	50 mm
Chuck capacity:	0 ÷ 13 mm
Distance from chuck to column:	104 mm
Package dimensions (L x W x H):	580 x 270 x 260 mm
Weight:	26 kg
Bar code:	3700209500499



Workbench with extensions and grooves to fix the vice. Lock vice included.



Laser pointing device for high precision drilling.



Drilling depth stop on the front side.

## **NEI** Drill presses