

Sliding compound mitresaw

Right / left double tilt - \varnothing 255 mm blade - laser pointing device

F36-258 DB

TOP LINE!

TECHNICAL FEATURES

Motor:	2000W - 230V
Speed	5500 RPM
Blade dimensions :	D 255 mm x d 30 mm
Cutting capacity at 0°:	340 x 82 mm
Angle cut at 45° right/left	240 x 82 mm
Compound cut at 45°:right/left	340 x 50 mm
Combined mitre/compound 45°+45° right/left:	240 x 25 mm

Angle automatic stops:	0° - 15° - 22.5° - 30- 45° right/left
Tilt stops:	0° and 45° right/left
Weight:	20 kg
Package dimensions (L x W x H)	920 x 570 x 375 mm
Bar code:	3700209502400

Available accessories : page 23



Double inclination, no need to rotate the piece to cut right / left!

- **Great cutting capacity (340 x 82 mm).**
- 2000 W "V" tilted motor.
- Circular base with rotation up to 45° left/right. Stopping devices at the main angles 0° - 15° - 22,5° - 30° - 45° right/left
- Integrated shaft locking device for a quick change of the blade.
- Two side extension bars to support big workpieces.



The double inclination allows angle and compound cuts at 0° and 45° right/left



Lock of the sliding position



Double laser to indicate the cutting line at the two sides of the blade

Standard equipment: double laser, clamp, two side and back extensions, 255 mm blade, dust bag