

Sliding compound mitresaw

Right / left double tilt - \varnothing 305 mm blade - laser pointing device

F36-259 DB

TOP LINE!



Standard equipment: double laser, clamp, two side and back extensions, 305 mm blade, dust bag.

Double inclination, no need to rotate the piece to cut right/left!

- **Great cutting capacity (340 x 105 mm)**
- Silent and powerful motor: 2000 W with belt transmission
- Double bar sliding movement
- Circular base with rotation up to 45° left/right. Stopping devices at the main angles 0° - 15° - 22,5° - 30° - 45° right/left
- Integrated shaft locking device for a quick change of the blade
- Two side extension bars to support big workpieces.
- Handle for the transport



The double inclination allows angle and compound cuts at 0° and 45° right/left

TECHNICAL FEATURES

Motor:	2000W - 230V
Speed	5500 RPM
Blade dimensions :	D 305 mm x d 30 mm
Cutting capacity at 0°:	340 x 105 mm
Angle cut at 45° right/left	240 x 105 mm
Compound cut at 45° right	340 x 40 mm
Compound cut at 45° left	340 x 65 mm
Combined mitre/compound 45° right/left +45° right/left:	240 x 40 mm

Angle automatic stops:	0° - 15° - 22,5° - 30- 45° right/left
Tilt stops:	0° and 45° right/left
Weight:	23 kg
Package dimensions (L x W x H)	915 x 570 x 535 mm
Bar code:	3700209503254

Available accessories : page 23



Double upper fence for a better head rigidity and a great cutting accuracy



Double laser to indicate the cutting line at the two sides of the blade